



# F 250 GX

## TECHNICAL DATASHEET F 250 GX



### GALAXY "GX"



For illustrative purposes only

### ENGINE

Description	FPT IVECO
Engine model	N67TE8P
Cylinders	6
RPM speed	1500
Cubic capacity	6.70 l
Air intake	Turbocharged
Standard voltage	24 Vdc
Optional voltage	Vdc
Sae	3-11
BMEP	2607 kPa
Cooling	Water
Flywheel P.R.P. Power net	216.0 kW
Flywheel Stand-by Power net	238.2 kW
Fuel Cons. at 100% (L.T.P.)	57.2 l/h
Fuel Cons. at 100% (P.R.P.)	51.5 l/h
Fuel Cons. at 75% (P.R.P.)	38.8 l/h
Fuel Cons. at 50% (P.R.P.)	24.9 l/h
Fuel Cons. at 25% (P.R.P.)	14.4 l/h
Electronic regulator	Standard
Precision class	G3
Oil quantity	17.0 l
Engine Antifreeze capacity	8.0 l
Radiator type	TR
Heat from radiator	135.0 kW
Heat from exhaust	152.1 kW
Heat from radiation	16.0 kW
Exhaust temperature	714 °C
Portata Raffreddamento	246.0 m³/min
Combustion air flow	12.8 m³/min
Exhaust gas flow	44.5 m³/min
TA Luft	N
TA Luft/2	N
EPA	N
Stage	N

### MAIN DATA

Continuous power (PRP)	<b>250.00</b> kVA
Continuous power (PRP)	<b>200.00</b> kW
Stand-by power (LTP)	<b>275.00</b> kVA
Stand-by power (LTP)	<b>220.00</b> kW
VAC - HZ - cos(fi)	<b>400 - 50 - 0.8</b>
Sound pressure 7 m.	<b>69</b> dBA

### DIMENSIONS AND WEIGHT

Width	1350 mm
Length	3770 mm
Height	2370 mm
Weight	2790 kg

### ALTERNATOR

Description	STAMFORD
Alternator model	UCDI274K
P.R.P. Power	250 kVA
L.T.P. Power	275 kVA
Connection	Series star
Phases	3FN
Winding	311
Terminal Number	12 nr.
IP Protection	23
Electronic regulator	AS440
Precision	1 ± %

### BASEFRAME

Model	GV121
Standard tank	500 l
Optional tank	0 l
Oversized tank*	0 l

### CANOPY & SILENCER

Canopy model	GV121
Silencer model	MSR/a 80
Silencer outlet diameter	89 mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0.850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

**P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer, according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

**L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.

