



For illustrative purposes only

### Strong points

- 1- Industrial diesel engine in genset version with certificate of origin
  - 2- Industrial brushless alternator with AVR
  - 3- Steel baseframe with retention basin, fuel tank with level sensor
  - 4- Soundproof canopy in galvanised, power coated sheet steel
  - 5- Soundproofing material made of high attenuation polyester fibre
  - 6- Exhaust silencer with insulated manifold
  - 7- Electrical panel mounted on board the unit with digital control device installed in metal box
  - 8- Compact for easy handling and use
  - 9- Test report, manuals and electrical drawings supplied
  - 10- World wide after sales service and technical support
- Further details on the technical data sheet**

### Performance

<b>Continuous power (PRP)</b>	<b>1350.0</b>	(kVA)
<b>Continuous power (PRP)</b>	<b>1080.0</b>	(kW)
<b>Stand-by power (LTP)</b>	<b>1455.0</b>	(kVA)
<b>Stand-by power (LTP)</b>	<b>1164.0</b>	(kW)
<b>Power factor</b>	<b>0.8</b>	

### Voltage

Frequency (Hz)	60	Hz
Voltage (V)	380	V

### Dimensions and noise level

Width	2360	mm
Length	8600	mm
Height	3540	mm
Weight	15000	kg
Sound pressure 7 m.	0.0	dBA

### Data references

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

**P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer, according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.  
**L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

### Engine

Engine brand	MITSUBISHI	
Engine model	S12R-PTA	
Cylinders	12	
Speed	1800	r.p.m.
Cubic capacity	49.03	l
Air intake	Turbocharged	
Standard voltage	24	Vdc
Optional voltage	Vdc	
Sae	00-21	
BMEP	1618	kPa
Cooling	Water	

### Engine power

Flywheel P.R.P. Power	1240.0	kW
Flywheel Stand-by Power	1370.0	kW

### Fuel consumption

Fuel Cons. at 100% (L.T.P.)	340.0	l/h
Fuel Cons. at 100% (P.R.P.)	302.0	l/h
Fuel Cons. at 75% (P.R.P.)	235.0	l/h
Fuel Cons. at 50% (P.R.P.)	170.0	l/h
Fuel Cons. at 25% (P.R.P.)	112.0	l/h

### Speed regulation

Electronic regulator	Standard
Precision class	A1

### Engine dimensions and liquids

Oil quantity	180.0	l
Engine Antifreeze capacity	125.0	l
Radiator standard	?	



# POWERFULL - DA 12 M



Gruppi Elettrogeni - Generating Sets  
 ГЕНЕРАТОРЫ ЭЛЕКТРИЧЕСТВА - مجموعة المولدات  
 Stromaggregate - Groupes Électrogènes - Grupos Electrógenos

## Heat from engine

Heat from radiator	708.0 kW
Heat from exhaust	852.0 kW
Heat from radiation	85.0 kW

## Exhaust data

Exhaust temperature	0 °C
Cooling air flow	1800.00 m <sup>3</sup> /min
Combustion air flow	97.00 m <sup>3</sup> /min
Exhaust gas flow	257.00 m <sup>3</sup> /min

## Emissions

TA Luft	Not available
TA Luft/2	Not available
EPA	Not available
Stage	Not available

## Alternator

Alternator brand	STAMFORD
Alternator model	PI734B
P.R.P. Power	1360.0 kVA
L.T.P. Power	1455.0 kVA

## Alternator wirings

Connection	Star
Phases	3PH+N
Winding	6 terminals winding 312
Terminal Number	6 nr.

## Alternator protection

IP Protection	23
---------------	----

## Voltage regulator

Electronic regulator	MX341
Precision	1.0 ± %

## Baseframe

Model	ST60
Standard tank	0 l
Optional tank	0 l
Oversized tank*	0 l

## Canopy & Silencer

Canopy model	C60
Silencer model	MSR/a 150
Silencer outlet diameter	168.0 mm

## Available control panels



Advanced **single gen-set controller for stand-by and prime power applications**. Direct communication with EFI engines, total remote monitoring and control, easy to install, configure and use, wide range of communication capabilities including: connection via RS232, RS485, CAN and on board USB, internet access using Ethernet, GPRS or 4G support for Modbus and SNMP protocols. Internal PLC support with PLC editor and monitor included in LiteEdit, cloud-based monitoring and control via Onis Visa WebSupervisor, active SMS and emails in different languages, SNMP traps, geofencing and tracking via Onis Visa WebSupervisor, 2x 10 A binary outputs for cranking and fuel solenoid, option for up to 16 additional binary inputs/outputs, flexible event based history with up to 350 events, load shedding, dummy load capability, tier 4 final support, automatic temperature based cooling/heating, comprehensive gen-set protections, multipurpose flexible timers, true RMS measurement.

## Optional control panels



**Guard Touch MANUAL OR AUTOMATIC** is the new revolutionary controller with touch screen, researched and developed by Visa S.p.A., which will be standard supply on our gensets. From a technical and operational viewpoint, the new device is different from its predecessors, but still maintains Visa's main characteristic: MODULARITY! Guard Touch is a versatile controller able to satisfy the myriad of requests from the end-user, from manual function to totally automatic management.

## Options

Each genset model has a wide range of accessories and customised equipment choices; standard equipment and optional accessories are described in the technical data sheet. Contact our sales office for further information and details.

