
TECHNICAL DATASHEET P 41 GO

P 41 GO

GALAXY “GO”



For illustrative purposes only

MAIN DATA

Continuous power (PRP)	**40.00**	kVA
Continuous power (PRP)	**32.00**	kW
Stand-by power (LTP)	**42.50**	kVA
Stand-by power (LTP)	**34.00**	kW
VAC - HZ - cos(fi)	**415 - 50 - 0.8**	

DIMENSIONS AND WEIGHT

Width	1010	mm
Length	2200	mm
Height	1460	mm
Weight	1090	kg

ENGINE

Description	PERKINS	
Engine model	1103A-33TG1	
Cylinders	3	
RPM speed	1500	
Cubic capacity	3.30	l
Air intake	Turbocharged	
Standard voltage	12	Vdc
Optional voltage	24	Vdc
Sae	3-11	
BMEP	1023	kPa
Cooling	Water	
Flywheel P.R.P. Power net	41.3	kW
Flywheel Stand-by Power net	45.6	kW
Fuel Cons. at 100% (L.T.P.)	11.8	l/h
Fuel Cons. at 100% (P.R.P)	10.5	l/h
Fuel Cons. at 75% (P.R.P.)	8.0	l/h
Fuel Cons. at 50% (P.R.P.)	5.6	l/h
Fuel Cons. at 25% (P.R.P.)	3.3	l/h
Electronic regulator	On request	
Precision class	G2	
Oil quantity	8.3	l
Engine Antifreeze capacity	4.4	l
Radiator type	TR	
Heat from radiator	26.0	kW
Heat from exhaust	30.0	kW
Heat from radiation	7.0	kW
Exhaust temperature	492	°C
Portata Raffreddamento	53.0	m³/min
Combustion air flow	2.9	m³/min
Exhaust gas flow	7.0	m³/min
TA Luft	N	
TA Luft/2	N	
EPA	N	
Stage	N	

ALTERNATOR

Description	DINGOL	
Alternator model	DG40	
P.R.P. Power	40	kVA
L.T.P. Power	42.5	kVA
Connection	Series star	
Phases	3FN	
Winding	311	
Terminal Number	12	nr.
IP Protection	23	
Electronic regulator	460	
Precision	2	± %

BASEFRAME

Model	GV030HD	
Standard tank	160	l
Optional tank	70	l
Oversized tank*	0	l

CANOPY & SILENCER

Canopy model	SENZA COFANO	
Silencer model	MS 12	
Silencer outlet diameter	60	mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

P.R.P. Prime Power-Continuous power at variable load: The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

L.T.P. Limited-time running power-Limited power: The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1.The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.