



### FOX "FOX"



For illustrative purposes only

### ENGINE

Description	PERKINS
Engine model	403A-11G1
Cylinders	3
RPM speed	1800
Cubic capacity	1.13 l
Air intake	Aspirated
Standard voltage	12 Vdc
Optional voltage	Vdc
Sae	5-6
BMEP	0 kPa
Cooling	Water
Flywheel P.R.P. Power net	10.3 kW
Flywheel Stand-by Power net	11.4 kW
Fuel Cons. at 100% (L.T.P.)	3.8 l/h
Fuel Cons. at 100% (P.R.P.)	3.1 l/h
Fuel Cons. at 75% (P.R.P.)	2.4 l/h
Fuel Cons. at 50% (P.R.P.)	1.8 l/h
Fuel Cons. at 25% (P.R.P.)	0.0 l/h
Electronic regulator	On request
Precision class	G2
Oil quantity	4.9 l
Engine Antifreeze capacity	3.3 l
Radiator type	TR
Heat from radiator	10.2 kW
Heat from exhaust	8.9 kW
Heat from radiation	2.6 kW
Exhaust temperature	437 °C
Portata Raffreddamento	35.4 m³/min
Combustion air flow	0.9 m³/min
Exhaust gas flow	2.2 m³/min
TA Luft	N
TA Luft/2	N
EPA	N
Stage	N

### MAIN DATA

Continuous power (PRP)	<b>11.20</b> kVA
Continuous power (PRP)	<b>8.96</b> kW
Stand-by power (LTP)	<b>12.40</b> kVA
Stand-by power (LTP)	<b>9.92</b> kW
VAC - HZ - cos(fi)	<b>208 - 60 - 0.8</b>
Sound pressure 7 m.	<b>65</b> dBA

### DIMENSIONS AND WEIGHT

Width	770 mm
Length	1470 mm
Height	1330 mm
Weight	530 kg

### ALTERNATOR

Description	STAMFORD
Alternator model	SOL1-L
P.R.P. Power	13.2 kVA
L.T.P. Power	14.5 kVA
Connection	Parallel star
Phases	3FN
Winding	311
Terminal Number	12 nr.
IP Protection	23
Electronic regulator	AS540
Precision	1 ± %

### BASEFRAME

Model	FOX
Standard tank	50 l
Optional tank	600 l
Oversized tank*	0 l

### CANOPY & SILENCER

Canopy model	FOX
Silencer model	F50/02
Silencer outlet diameter	50 mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0.850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

**P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer, according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

**L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.

