
TECHNICAL DATASHEET D 210 B

D 210 B

POWERFULL “B”



For illustrative purposes only

MAIN DATA

Continuous power (PRP)	**200.00**	kVA
Continuous power (PRP)	**160.00**	kW
Stand-by power (LTP)	**220.00**	kVA
Stand-by power (LTP)	**176.00**	kW
VAC - HZ - cos(fi)	**415 - 50 - 0.8**	

DIMENSIONS AND WEIGHT

Width	1120	mm
Length	2600	mm
Height	1910	mm
Weight	2000	kg

ENGINE

Description	DEUTZ	
Engine model	BF6M1013FCG3	
Cylinders	6	
RPM speed	1500	
Cubic capacity	7.15	l
Air intake	Turbocharged	
Standard voltage	12	Vdc
Optional voltage	24	Vdc
Sae	2-11	
BMEP	2250	kPa
Cooling	Water	
Flywheel P.R.P. Power net	174.6	kW
Flywheel Stand-by Power net	193.8	kW
Fuel Cons. at 100% (L.T.P.)	56.0	l/h
Fuel Cons. at 100% (P.R.P)	50.8	l/h
Fuel Cons. at 75% (P.R.P.)	37.7	l/h
Fuel Cons. at 50% (P.R.P.)	25.3	l/h
Fuel Cons. at 25% (P.R.P.)	13.1	l/h
Electronic regulator	Standard	
Precision class	G3	
Oil quantity	20.0	l
Engine Antifreeze capacity	9.8	l
Radiator type	TR	
Heat from radiator	96.1	kW
Heat from exhaust	0.0	kW
Heat from radiation	20.0	kW
Exhaust temperature	530	°C
Portata Raffreddamento	192.0	m³/min
Combustion air flow	0.0	m³/min
Exhaust gas flow	35.2	m³/min
TA Luft	N	
TA Luft/2	N	
EPA	N	
Stage	2	

ALTERNATOR

Description	STAMFORD	
Alternator model	UCI274H	
P.R.P. Power	200	kVA
L.T.P. Power	220	kVA
Connection	Series star	
Phases	3FN	
Winding	311	
Terminal Number	12	nr.
IP Protection	23	
Electronic regulator	AS440	
Precision	1	± %

BASEFRAME

Model	T2	
Standard tank	520	l
Optional tank	0	l
Oversized tank*	0	l

CANOPY & SILENCER

Canopy model	SENZA COFANO	
Silencer model	MS 25	
Silencer outlet diameter	114	mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

P.R.P. Prime Power-Continuous power at variable load: The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

L.T.P. Limited-time running power-Limited power: The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1.The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.