



# DS 900 GX

## TECHNICAL DATASHEET DS 900 GX



### GALAXY "GX"



For illustrative purposes only

### ENGINE

Description	DOOSAN
Engine model	DP222CC
Cylinders	12
RPM speed	1500
Cubic capacity	21.93 l
Air intake	Turbocharged
Standard voltage	24 Vdc
Optional voltage	Vdc
Sae	0-18
BMEP	1880 kPa
Cooling	Water
Flywheel P.R.P. Power net	768.8 kW
Flywheel Stand-by Power net	853.8 kW
Fuel Cons. at 100% (L.T.P.)	205.0 l/h
Fuel Cons. at 100% (P.R.P.)	183.0 l/h
Fuel Cons. at 75% (P.R.P.)	137.0 l/h
Fuel Cons. at 50% (P.R.P.)	99.0 l/h
Fuel Cons. at 25% (P.R.P.)	54.0 l/h
Electronic regulator	Standard
Precision class	G3
Oil quantity	75.0 l
Engine Antifreeze capacity	24.0 l
Radiator type	TE
Heat from radiator	549.0 kW
Heat from exhaust	618.2 kW
Heat from radiation	66.6 kW
Exhaust temperature	574 °C
Portata Raffreddamento	984.0 m³/min
Combustion air flow	49.3 m³/min
Exhaust gas flow	124.2 m³/min
TA Luft	N
TA Luft/2	N
EPA	N
Stage	N

### MAIN DATA

Continuous power (PRP)	<b>910.00</b> kVA
Continuous power (PRP)	<b>728.00</b> kW
Stand-by power (LTP)	<b>1000.00</b> kVA
Stand-by power (LTP)	<b>800.00</b> kW
VAC - HZ - cos(fi)	<b>400 - 50 - 0.8</b>
Sound pressure 7 m.	<b>72</b> dBA

### DIMENSIONS AND WEIGHT

Width	1940 mm
Length	5800 mm
Height	2550 mm
Weight	0 kg

### ALTERNATOR

Description	STAMFORD
Alternator model	S6L1D-D
P.R.P. Power	940 kVA
L.T.P. Power	1010 kVA
Connection	Star
Phases	3FN
Winding	312
Terminal Number	6 nr.
IP Protection	23
Electronic regulator	MX322
Precision	0.5 ± %

### BASEFRAME

Model	GV300
Standard tank	400 l
Optional tank	0 l
Oversized tank*	0 l

### CANOPY & SILENCER

Canopy model	GV300
Silencer model	MSR/A 250
Silencer outlet diameter	273 mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0.850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

**P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer, according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

**L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.

