



### POWERFULL "B"



For illustrative purposes only

#### ENGINE

Description	FPT IVECO
Engine model	C13TE2F
Cylinders	6
RPM speed	1800
Cubic capacity	12.88 l
Air intake	Turbocharged
Standard voltage	24 Vdc
Optional voltage	Vdc
Sae	1-14
BMEP	2540 kPa
Cooling	Water
Flywheel P.R.P. Power net	300.0 kW
Flywheel Stand-by Power net	334.0 kW
Fuel Cons. at 100% (L.T.P.)	91.3 l/h
Fuel Cons. at 100% (P.R.P.)	91.3 l/h
Fuel Cons. at 75% (P.R.P.)	70.1 l/h
Fuel Cons. at 50% (P.R.P.)	50.0 l/h
Fuel Cons. at 25% (P.R.P.)	0.0 l/h
Electronic regulator	Standard
Precision class	G3
Oil quantity	35.0 l
Engine Antifreeze capacity	19.5 l
Radiator type	TE
Heat from radiator	0.0 kW
Heat from exhaust	0.0 kW
Heat from radiation	0.0 kW
Exhaust temperature	520 °C
Portata Raffreddamento	0.0 m³/min
Combustion air flow	0.0 m³/min
Exhaust gas flow	72.2 m³/min
TA Luft	N
TA Luft/2	N
EPA	N
Stage	N

#### MAIN DATA

Continuous power (PRP)	<b>350.00</b> kVA
Continuous power (PRP)	<b>280.00</b> kW
Stand-by power (LTP)	<b>390.00</b> kVA
Stand-by power (LTP)	<b>312.00</b> kW
VAC - HZ - cos(fi)	<b>208 - 60 - 0.8</b>

#### DIMENSIONS AND WEIGHT

#### ALTERNATOR

Description	STAMFORD
Alternator model	S4L1D-E
P.R.P. Power	400 kVA
L.T.P. Power	435 kVA
Connection	Parallel star
Phases	3FN
Winding	311
Terminal Number	12 nr.
IP Protection	23
Electronic regulator	AS440
Precision	1 ± %

#### BASEFRAME

Model	T3
Standard tank	900 l
Optional tank	0 l
Oversized tank*	0 l

#### CANOPY & SILENCER

Canopy model	SENZA COFANO
Silencer model	MS 25
Silencer outlet diameter	114 mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0.850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

**P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer, according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

**L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.

