



### POWERFULL "U"



For illustrative purposes only

### ENGINE

Description	BAUDOUIN
Engine model	16M33G1900/5
Cylinders	16
RPM speed	1500
Cubic capacity	52.30 l
Air intake	Turbocharged
Standard voltage	24 Vdc
Optional voltage	Vdc
Sae	0-18
BMEP	2560 kPa
Cooling	Water
Flywheel P.R.P. Power net	1530.0 kW
Flywheel Stand-by Power net	1650.0 kW
Fuel Cons. at 100% (L.T.P.)	400.3 l/h
Fuel Cons. at 100% (P.R.P.)	358.2 l/h
Fuel Cons. at 75% (P.R.P.)	260.3 l/h
Fuel Cons. at 50% (P.R.P.)	176.2 l/h
Fuel Cons. at 25% (P.R.P.)	97.9 l/h
Electronic regulator	Standard
Precision class	
Oil quantity	175.0 l
Engine Antifreeze capacity	130.0 l
Radiator type	TE
Heat from radiator	2579.3 kW
Heat from exhaust	0.0 kW
Heat from radiation	0.0 kW
Exhaust temperature	550 °C
	0.0
Combustion air flow	110.8 m³/min
Exhaust gas flow	378.0 m³/min
TA Luft	N
TA Luft/2	N
EPA	N
Stage	N

### MAIN DATA

Continuous power (PRP)	<b>1750.00</b> kVA
Continuous power (PRP)	<b>1400.00</b> kW
Stand-by power (LTP)	<b>1900.00</b> kVA
Stand-by power (LTP)	<b>1520.00</b> kW
VAC - HZ - cos(fi)	<b>400 - 50 - 0.8</b>

### DIMENSIONS AND WEIGHT

Width	2220 mm
Length	5400 mm
Height	2700 mm
Weight	11600 kg

### ALTERNATOR

Description	STAMFORD
Alternator model	S7L1D-F
P.R.P. Power	1900 kVA
L.T.P. Power	2035 kVA
Connection	Star
Phases	3FN
Winding	312
Terminal Number	6 nr.
IP Protection	23
Electronic regulator	MX341
Precision	1 ± %

### BASEFRAME

Model	ST60
Standard tank	0 l
Optional tank	0 l
Oversized tank*	0 l

### CANOPY & SILENCER

Canopy model	SENZA COFANO
Silencer model	MS 50
Silencer outlet diameter	273 mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0.850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

**P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer, according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

**L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.

