



POWERFULL "U"



For illustrative purposes only

ENGINE

Description	BAUDOUIN
Engine model	12M33G1250/5
Cylinders	12
RPM speed	1500
Cubic capacity	39.20 l
Air intake	Turbocharged
Standard voltage	24 Vdc
Optional voltage	Vdc
Sae	0-18
BMEP	2261 kPa
Cooling	Water
Flywheel P.R.P. Power net	1007.0 kW
Flywheel Stand-by Power net	1108.0 kW
Fuel Cons. at 100% (L.T.P.)	262.6 l/h
Fuel Cons. at 100% (P.R.P.)	236.2 l/h
Fuel Cons. at 75% (P.R.P.)	175.0 l/h
Fuel Cons. at 50% (P.R.P.)	119.5 l/h
Fuel Cons. at 25% (P.R.P.)	66.4 l/h
Electronic regulator	Standard
Precision class	G3
Oil quantity	155.0 l
Engine Antifreeze capacity	83.0 l
Radiator type	TE
Heat from radiator	1518.5 kW
Heat from exhaust	0.0 kW
Heat from radiation	0.0 kW
Exhaust temperature	550 °C
Portata Raffreddamento	1140.0 m³/min
Combustion air flow	74.1 m³/min
Exhaust gas flow	212.0 m³/min
TA Luft	N
TA Luft/2	N
EPA	N
Stage	N

MAIN DATA

Continuous power (PRP)	1150.00 kVA
Continuous power (PRP)	920.00 kW
Stand-by power (LTP)	1250.00 kVA
Stand-by power (LTP)	1000.00 kW
VAC - HZ - cos(fi)	400 - 50 - 0.8

DIMENSIONS AND WEIGHT

ALTERNATOR

Description	STAMFORD
Alternator model	S6L1D-G
P.R.P. Power	1260 kVA
L.T.P. Power	1345 kVA
Connection	Star
Phases	3FN
Winding	312
Terminal Number	6 nr.
IP Protection	23
Electronic regulator	MX322
Precision	0.5 ± %

BASEFRAME

Model	ST60
Standard tank	0 l
Optional tank	0 l
Oversized tank*	0 l

CANOPY & SILENCER

Canopy model	SENZA COFANO
Silencer model	MS 45
Silencer outlet diameter	219 mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0.850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

P.R.P. Prime Power-Continuous power at variable load: The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer, according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

L.T.P. Limited-time running power-Limited power: The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.

