


P 14 B





POWERFULL "B"



For illustrative purposes only

Tor mustrative purposes only		
ENGINE		
Description	PERKINS	
Engine model	403A-15G1	
Cylinders	3	
RPM speed	1800	
Cubic capacity	1.50	1
Air intake	Aspirated	
Standard voltage	12	Vdc
Optional voltage		Vdc
Sae	4-71/2	
ВМЕР	650	kPa
Cooling	Water	
Flywheel P.R.P. Power net	14.4	kW
Flywheel E.P. Power net	15.9	kW
Fuel Cons. at 100% (E.P.)	4.8	l/h
Fuel Cons. at 100% (P.R.P)	4.3	l/h
Fuel Cons. at 75% (P.R.P.)	3.3	l/h
Fuel Cons. at 50% (P.R.P.)	2.4	l/h
Fuel Cons. at 25% (P.R.P.)	0.0	l/h
Electronic regulator	On request	
Precision class	G2	
Oil quantity	6.0	I
Engine Antifreeze capacity	2.6	Ī
Radiator type	TR	
Heat from radiator	13.6	kW
Heat from exhaust	10.3	kW
Heat from radiation	4.0	kW
Exhaust temperature	455	°C
Cooling air flow	34.8	m³/min
Combustion air flow	1.2	m³/min
Exhaust gas flow	3.1	m³/min
TA Luft	N	
TA Luft/2	N	
EPA	N	
Stage	N	

MAIN DATA		
Continuous power (PRP)	15.80	kVA
Continuous power (PRP)	12.64	kW
Emergency power (E.P.)	17.50	kVA
Emergency power (E.P.)	14.00	kW
VAC - HZ - cos(fi)	220 - 60 - 0.8	

DIMENSIONS AND WEIGHT		
Width	700	mm
Length	1240	mm
Height	1170	mm
Weight	460	kg

ALTERNATOR		
Description	STAMFORD	
Alternator model	S0L1-P	
P.R.P. Power	16.8	kVA
E.P. Power	18.5	kVA
Connection	Parallel star	
Phases	3FN	
Winding	311	
Terminal Number	12	nr.
IP Protection	23	
Electronic regulator	AS540	
Precision	1.0	± %

BASEFRAME	
Model	T0
Standard tank	70 I
Optional tank	0
Oversized tank*	0 1

CANOPY & SILENCER		
Canopy model	SENZA COFANO	
Silencer model	MS 10	
Silencer outlet diameter	48.0	mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance. P.R.P. Prime Power-Continuous power at variable load: The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer. E.P. - Emergency power: This is the maximum power that a generating set can deliver for a limited number of hours per year while complying with the maintenance frequency stipulated under the environmental conditions set by the Manufacturer. The number of hours per year is determined by the engine manufacturer. The average power output over time must be lower than the percentages set by the engine manufacturer. Overloading is not allowed.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.