

F 301 GX





GALAXY "GX"



For	illustrativ	ve nur	noses	only

ENGINE		
Description	FPT IVECO	
Engine model	C87TE4	
Cylinders	6	
RPM speed	1500	
Cubic capacity	8.70	I
Air intake	Turbocharged	
Standard voltage	24	Vdc
Optional voltage		Vdc
Sae	1-14	
BMEP	0	kPa
Cooling	Water	
Flywheel P.R.P. Power net	275.0	kW
Flywheel E.P. Power net	299.0	kW
Fuel Cons. at 100% (E.P.)	72.4	l/h
Fuel Cons. at 100% (P.R.P)	66.6	l/h
Fuel Cons. at 75% (P.R.P.)	49.3	l/h
Fuel Cons. at 50% (P.R.P.)	37.3	l/h
Fuel Cons. at 25% (P.R.P.)	0.0	l/h
Electronic regulator	Standard	
Precision class	G3	
Oil quantity	28.0	I
Engine Antifreeze capacity	15.0	I
Radiator type	TR	
Heat from radiator	202.0	kW
Heat from exhaust	238.0	kW
Heat from radiation	25.0	kW
Exhaust temperature	488	°C
Cooling air flow	340.0	m³/min
Combustion air flow	18.1	m³/min
Exhaust gas flow	49.4	m³/min
TA Luft	N	
TA Luft/2	N	
EPA	N	
Stage	N	

MAIN DATA	
Continuous power (PRP)	300.00 kVA
Continuous power (PRP)	240.00 kW
Emergency power (E.P.)	330.00 kVA
Emergency power (E.P.)	264.00 kW
VAC - HZ - cos(fi)	400 - 50 - 0.8
Sound pressure 7 m.	72.0 dBA

DIMENSIONS AND WEIGHT		
Width	1350 mm	
Length	4270 mm	
Height	2370 mm	
Weight	3350 kg	

ALTERNATOR	
Description	MECC ALTE
Alternator model	ECO38-2LN/4
P.R.P. Power	300.0 kVA
E.P. Power	330.0 kVA
Connection	Series star
Phases	3FN
Winding	12STD
Terminal Number	12 nr.
IP Protection	23
Electronic regulator	DSR
Precision	1.0 ± %

BASEFRAME	
Model	GV121
Standard tank	500 I
Optional tank	0 1
Oversized tank*	0

CANOPY & SILENCER		
Canopy model	GV121/00/1	
Silencer model	MSR/a 100	
Silencer outlet diameter	114.0	mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance. P.R.P. Prime Power-Continuous power at variable load: The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer. E.P. - Emergency power: This is the maximum power that a generating set can deliver for a limited number of hours per year while complying with the maintenance frequency stipulated under the environmental conditions set by the Manufacturer. The number of hours per year is determined by the engine manufacturer. The average power output over time must be lower than the percentages set by the engine manufacturer. Overloading is not allowed.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.