## **TECHNICAL DATASHEET V 350 GX**



## V 350 GX





## GALAXY "GX"



	 	- 1-	e je	 

ENGINE		
Description	VOLVO-PENTA	
Engine model	TAD1342GE-B	
Cylinders	6	
RPM speed	1800	
Cubic capacity		I
Air intake	Turbocharged	
Standard voltage	24	Vdc
Optional voltage		Vdc
Sae	1-14	
BMEP	1900	kPa
Cooling	Water	
Flywheel P.R.P. Power net	345.0	kW
Flywheel E.P. Power net	377.0	kW
Fuel Cons. at 100% (E.P.)	90.2	l/h
Fuel Cons. at 100% (P.R.P)	82.6	l/h
Fuel Cons. at 75% (P.R.P.)	61.6	l/h
Fuel Cons. at 50% (P.R.P.)	42.5	l/h
Fuel Cons. at 25% (P.R.P.)	24.3	l/h
Electronic regulator	Standard	
Precision class	G3	
Oil quantity	36.0	I
Engine Antifreeze capacity	0.0	I
Radiator type	TR	
Heat from radiator	159.0	kW
Heat from exhaust	253.0	kW
Heat from radiation	0.0	kW
Exhaust temperature	432	°C
Cooling air flow	0.0	m³/min
Combustion air flow	28.7	m³/min
Exhaust gas flow	0.0	m³/min
TA Luft	N	
TA Luft/2	N	
EPA	N	
Stage	N	

MAIN DATA	
Continuous power (PRP)	<b>401.00</b> kVA
Continuous power (PRP)	<b>320.80</b> kW
Emergency power (E.P.)	<b>438.00</b> kVA
Emergency power (E.P.)	<b>350.40</b> kW
VAC - HZ - cos(fi)	480 - 60 - 0.8
Sound pressure 7 m.	<b>72.0</b> dBA

DIMENSIONS AND WEIGHT			
Width	1600 mm		
Length	4310 mm		
Height	2560 mm		
Weight	4780 kg		

ALTERNATOR			
Description	STAMFORD		
Alternator model	S4L1D-E		
P.R.P. Power	455.0	kVA	
E.P. Power	490.0	kVA	
Connection	Series star		
Phases	3FN		
Winding	311		
Terminal Number	12	nr.	
IP Protection	23		
Electronic regulator	AS440		
Precision	1.0	± %	

BASEFRAME	
Model	GV151/00/00
Standard tank	800 I
Optional tank	0 1
Oversized tank*	1800 I

CANOPY & SILENCER			
Canopy model	GV151		
Silencer model	MSR/a 125		
Silencer outlet diameter	140 0 mm		

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance. P.R.P. Prime Power-Continuous power at variable load: The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer. E.P. - Emergency power: This is the maximum power that a generating set can deliver for a limited number of hours per year while complying with the maintenance frequency stipulated under the environmental conditions set by the Manufacturer. The number of hours per year is determined by the engine manufacturer. The average power output over time must be lower than the percentages set by the engine manufacturer. Overloading is not allowed.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.