

F 103 GX





GALAXY "GX"



٠.		baib	0000	01111

Description FPT IVECO Engine model N45TE2PV Cylinders 4 RPM speed 1500 Cubic capacity 4.50 Air intake Turbocharged Standard voltage 12 Vdc Optional voltage 24 Vdc Sae 3-11½ BMEP 1777 kPa Cooling Water Flywheel P.R.P. Power net 89.2 kW Flywheel E.P. Power net 98.2 kW Fuel Cons. at 100% (E.P.) 24.8 l/h Fuel Cons. at 100% (P.R.P) 22.8 l/h Fuel Cons. at 50% (P.R.P.) 11.3 l/h Fuel Cons. at 25% (P.R.P.) 11.3 l/h Fuel Cons. at 25% (P.R.P.) 51.3 l/h Fuel Cons class G3 Oil quantity 12.8 l Engine Antifreeze capacity 8.5 l Radiator type TR Heat from radiator 0.0 kW Heat from radiation 0.0 kW Exhaust temperature 0 °C Cooling air flow 0.0 m³/min Combustion air flow 8.8 m³/min Exhaust gas flow 19.0 m³/min TA Luft N TA Luft/2 N Staqe	ENGINE		
Engine model N45TE2PV Cylinders		FDT IVECO	
Cylinders 4 RPM speed 1500 Cubic capacity 4.50 Air intake Turbocharged Standard voltage 12 Vdc Optional voltage 24 Vdc Sae 3-11½ BMEP 1777 kPa Cooling Water Flywheel P.R.P. Power net 89.2 kW Flywheel E.P. Power net 98.2 kW Fuel Cons. at 100% (E.P.) 24.8 l/h Fuel Cons. at 100% (P.R.P) 22.8 l/h Fuel Cons. at 50% (P.R.P.) 11.3 l/h Fuel Cons. at 50% (P.R.P.) 11.3 l/h Fuel Cons. at 52% (P.R.P.) 0.0 l/h Fuel Cons. at 52% (P.R.P.) 3 0.0 l/h Fuel Cons. at 50% (P.R.P.) 11.3 l/h Fuel Cons. at 50% (P.R.P.) 0.0 l/h Fuel Cons. at 50% (P.R.P.) 11.3 l/h Fuel Cons. at 50% (P.R.P.) 0.0 l/h Electronic regulator Standard Precision cla			
RPM speed 1500 Cubic capacity 4.50 Air intake Turbocharged Standard voltage 12 Vdc Optional voltage 24 Vdc Sae 3-11½ BMEP 1777 kPa Cooling Water Flywheel P.R.P. Power net 89.2 kW kW Flywheel E.P. Power net 98.2 kW Fuel Cons. at 100% (E.P.) 24.8 l/h I/h Fuel Cons. at 100% (P.R.P) 22.8 l/h I/h Fuel Cons. at 55% (P.R.P.) 18.7 l/h I/h Fuel Cons. at 50% (P.R.P.) 11.3 l/h I/h Fuel Cons. at 25% (P.R.P.) 11.3 l/h I/h Fuel Cons. at 25% (P.R.P.) 11.3 l/h I/h Fuel Cons. at 25% (P.R.P.) 12.8 l I Electronic regulator Standard Precision class G3 OI I/h Electronic regulator Standard Precision class G3 OI I/h Electronic regulator Standard Precision class I Redulator type TR Heat from radiator 0.0 kW W Heat from radiator 0.0 kW W Heat			
Cubic capacity 4.50 Air intake Turbocharged Standard voltage 12 Vdc Optional voltage 24 Vdc Sae 3-11½ BMEP 1777 kPa Cooling Water Flywheel P.R.P. Power net 89.2 kW Flywheel E.P. Power net 98.2 kW Fuel Cons. at 100% (E.P.) 24.8 I/h Fuel Cons. at 75% (P.R.P.) 18.7 I/h Fuel Cons. at 75% (P.R.P.) 11.3 I/h Fuel Cons. at 25% (P.R.P.) 0.0 I/h Electronic regulator Standard Precision class G3 Oil quantity 12.8 I Engine Antifreeze capacity 8.5 I Radiator type TR Heat from radiator 0.0 kW Heat from exhaust 0.0 kW Exhaust temperature 0 °C Cooling air flow 0.0 m³/min Combustion air flow 8.8 m³/min Exhaust gas flow 19.0 m³/min TA Luft N EPA N		•	
Air intake Standard voltage 12 Vdc Optional voltage 24 Vdc Sae 3-11½ BMEP 1777 kPa Cooling Water Flywheel P.R.P. Power net 89.2 kW Flywheel E.P. Power net 98.2 kW Fuel Cons. at 100% (E.P.) 24.8 l/h Fuel Cons. at 100% (P.R.P) 22.8 l/h Fuel Cons. at 75% (P.R.P.) 18.7 l/h Fuel Cons. at 50% (P.R.P.) 11.3 l/h Fuel Cons. at 25% (P.R.P.) 0.0 l/h Electronic regulator Standard Precision class G3 Oil quantity 12.8 l Engine Antifreeze capacity 8.5 l Radiator type TR Heat from radiator 0.0 kW Heat from exhaust 0.0 kW Exhaust temperature 0 °C Cooling air flow 0.0 m³/min Combustion air flow 8.8 m³/min Exhaust gas flow 19.0 m³/min TA Luft N TA Luft/2 N			
Standard voltage 12 Vdc Optional voltage 24 Vdc Sae 3-11½ BMEP 1777 kPa Cooling Water Flywheel P.R.P. Power net 89.2 kW Flywheel E.P. Power net 98.2 kW Fuel Cons. at 100% (E.P.) 24.8 l/h Fuel Cons. at 100% (P.R.P) 22.8 l/h Fuel Cons. at 75% (P.R.P.) 18.7 l/h Fuel Cons. at 50% (P.R.P.) 11.3 l/h Fuel Cons. at 25% (P.R.P.) 0.0 l/h Electronic regulator Standard Precision class G3 Oil quantity 12.8 l Engine Antifreeze capacity 8.5 l Radiator type TR Heat from radiator 0.0 kW Heat from radiation 0.0 kW Exhaust temperature 0 °C Cooling air flow 0.0 m³/min Combustion air flow 8.8 m³/min Exhaust gas flow 19.0 m³/min TA Luft/2 N EPA N	Cubic capacity	4.50	I
Optional voltage 24 Vdc Sae 3-11½ BMEP 1777 kPa Cooling Water Flywheel P.R.P. Power net 89.2 kW Flywheel E.P. Power net 98.2 kW Fuel Cons. at 100% (E.P.) 24.8 l/h Fuel Cons. at 100% (P.R.P) 22.8 l/h Fuel Cons. at 75% (P.R.P.) 18.7 l/h Fuel Cons. at 50% (P.R.P.) 11.3 l/h Fuel Cons. at 25% (P.R.P.) 0.0 l/h Electronic regulator Standard Precision class G3 Oil quantity 12.8 l Engine Antifreeze capacity 8.5 l Radiator type TR Heat from radiator 0.0 kW Heat from exhaust 0.0 kW Heat from radiation 0.0 kW Exhaust temperature 0 °C Cooling air flow 0.0 m³/min Combustion air flow 8.8 m³/min Exhaust gas flow 19.0 m³/min TA Luft/2 N EPA N	Air intake	Turbocharged	
Sae 3-11½ BMEP 1777 kPa Cooling Water Flywheel P.R.P. Power net 89.2 kW Flywheel E.P. Power net 98.2 kW Fuel Cons. at 100% (E.P.) 24.8 l/h Fuel Cons. at 100% (P.R.P) 22.8 l/h Fuel Cons. at 75% (P.R.P.) 18.7 l/h Fuel Cons. at 50% (P.R.P.) 11.3 l/h Fuel Cons. at 25% (P.R.P.) 0.0 l/h Electronic regulator Standard Precision class G3 Oil quantity 12.8 l Engine Antifreeze capacity 8.5 l Radiator type TR Heat from radiator 0.0 kW Heat from exhaust 0.0 kW Heat from radiation 0.0 kW Exhaust temperature 0 °C Cooling air flow 0.0 m³/min Combustion air flow 8.8 m³/min Exhaust gas flow 19.0 m³/min TA Luft N TA Luft/2 N EPA N	Standard voltage	12	Vdc
BMEP 1777 kPa Cooling Water Flywheel P.R.P. Power net 89.2 kW Flywheel E.P. Power net 98.2 kW Fuel Cons. at 100% (E.P.) 24.8 I/h Fuel Cons. at 100% (P.R.P) 18.7 I/h Fuel Cons. at 55% (P.R.P.) 11.3 I/h Fuel Cons. at 25% (P.R.P.) 0.0 I/h Fuel Cons. at 25% (P.R.P.) 0.0 I/h Electronic regulator Standard Precision class G3 Oil quantity 12.8 I Engine Antifreeze capacity 8.5 I Radiator type TR Heat from radiator 0.0 kW Heat from exhaust 0.0 kW Heat from radiation 0.0 kW Exhaust temperature 0 °C Cooling air flow 0.0 m³/min Exhaust gas flow 19.0 m³/min TA Luft N TA Luft/2 N	Optional voltage	24	Vdc
Cooling Water Flywheel P.R.P. Power net 89.2 kW Flywheel E.P. Power net 98.2 kW Fuel Cons. at 100% (E.P.) 24.8 l/h Fuel Cons. at 100% (P.R.P) 22.8 l/h Fuel Cons. at 75% (P.R.P.) 18.7 l/h Fuel Cons. at 50% (P.R.P.) 11.3 l/h Fuel Cons. at 25% (P.R.P.) 0.0 l/h Electronic regulator Standard Precision class G3 Oil quantity 12.8 l Engine Antifreeze capacity 8.5 l Radiator type TR Heat from radiator 0.0 kW Heat from exhaust 0.0 kW Heat from radiation 0.0 kW Exhaust temperature 0 °C Cooling air flow 0.0 m³/min Combustion air flow 8.8 m³/min Exhaust gas flow 19.0 m³/min TA Luft N TA Luft/2 N EPA N	Sae	3-11½	
Flywheel P.R.P. Power net 89.2 kW Flywheel E.P. Power net 98.2 kW Fuel Cons. at 100% (E.P.) 24.8 l/h Fuel Cons. at 100% (P.R.P) 22.8 l/h Fuel Cons. at 75% (P.R.P.) 18.7 l/h Fuel Cons. at 50% (P.R.P.) 11.3 l/h Fuel Cons. at 25% (P.R.P.) 0.0 l/h Electronic regulator Standard Precision class G3 Oil quantity 12.8 l Engine Antifreeze capacity 8.5 l Radiator type TR Heat from radiator 0.0 kW Heat from exhaust 0.0 kW Exhaust temperature 0 °C Cooling air flow 0.0 m³/min Combustion air flow 8.8 m³/min Exhaust gas flow 19.0 m³/min TA Luft N TA Luft/2 N EPA N	BMEP	1777	kPa
Flywheel E.P. Power net Fluel Cons. at 100% (E.P.) Fuel Cons. at 100% (P.R.P) Fuel Cons. at 75% (P.R.P.) Fuel Cons. at 50% (P.R.P.) Fuel Cons. at 50% (P.R.P.) Fuel Cons. at 55% (P.R.P.) Fuel Cons. at 25% (P.R.P.) Fuel Cons. at 50% (P.R.P.) Fuel Cons. at 50% (P.R.P.) Fuel Cons. at 75% (P.R.P.) Fuel Cons. at 100% (P.R.P.) Fuel Cons. at 50% (P.R.P.) Fu	Cooling	Water	
Fuel Cons. at 100% (E.P.) 24.8 l/h Fuel Cons. at 100% (P.R.P) 22.8 l/h Fuel Cons. at 75% (P.R.P.) 18.7 l/h Fuel Cons. at 50% (P.R.P.) 11.3 l/h Fuel Cons. at 25% (P.R.P.) 0.0 l/h Electronic regulator Standard Precision class G3 Oil quantity 12.8 l Engine Antifreeze capacity 8.5 l Radiator type TR Heat from radiator 0.0 kW Heat from exhaust 0.0 kW Heat from radiation 0.0 kW Exhaust temperature 0 °C Cooling air flow 0.0 m³/min Combustion air flow 8.8 m³/min Exhaust gas flow 19.0 m³/min TA Luft N TA Luft/2 N EPA N	Flywheel P.R.P. Power net	89.2	kW
Fuel Cons. at 100% (P.R.P) 22.8 l/h Fuel Cons. at 75% (P.R.P.) 18.7 l/h Fuel Cons. at 50% (P.R.P.) 11.3 l/h Fuel Cons. at 25% (P.R.P.) 0.0 l/h Electronic regulator Standard Precision class G3 Oil quantity 12.8 l Engine Antifreeze capacity 8.5 l Radiator type TR Heat from radiator 0.0 kW Heat from exhaust 0.0 kW Heat from radiation 0.0 kW Exhaust temperature 0 °C Cooling air flow 0.0 m³/min Combustion air flow 8.8 m³/min Exhaust gas flow 19.0 m³/min TA Luft N TA Luft/2 N EPA N	Flywheel E.P. Power net	98.2	kW
Fuel Cons. at 75% (P.R.P.) 18.7 I/h Fuel Cons. at 50% (P.R.P.) 11.3 I/h Fuel Cons. at 25% (P.R.P.) 0.0 I/h Electronic regulator Standard Precision class G3 Oil quantity 12.8 I Engine Antifreeze capacity 8.5 I Radiator type TR Heat from radiator 0.0 kW Heat from exhaust 0.0 kW Heat from radiation 0.0 kW Exhaust temperature 0 °C Cooling air flow 0.0 m³/min Combustion air flow 8.8 m³/min Exhaust gas flow 19.0 m³/min TA Luft N N EPA N	Fuel Cons. at 100% (E.P.)	24.8	l/h
Fuel Cons. at 50% (P.R.P.) 11.3 l/h Fuel Cons. at 25% (P.R.P.) 0.0 l/h Electronic regulator Standard Precision class G3 Oil quantity 12.8 l Engine Antifreeze capacity 8.5 l Radiator type TR Heat from radiator 0.0 kW Heat from exhaust 0.0 kW Exhaust temperature 0 °C Cooling air flow 0.0 m³/min Combustion air flow 8.8 m³/min Exhaust gas flow 19.0 m³/min TA Luft N TA Luft/2 N EPA N	Fuel Cons. at 100% (P.R.P)	22.8	l/h
Fuel Cons. at 25% (P.R.P.) Electronic regulator Precision class G3 Oil quantity 12.8 Engine Antifreeze capacity Radiator type TR Heat from radiator Heat from exhaust Heat from radiation Exhaust temperature Cooling air flow Combustion air flow Exhaust gas flow TA Luft TA Luft TA Luft/2 EPA S G3 Oil quantity 12.8 18 O 3 N Exhaust I Engine Antifreeze capacity 8.5 Radiator type TR TR Heat from radiator 0.0 kW EXW EXW EXW EXW EXW EXW EXW E	Fuel Cons. at 75% (P.R.P.)	18.7	l/h
Electronic regulator Precision class G3 Oil quantity 12.8 I Engine Antifreeze capacity 8.5 I Radiator type TR Heat from radiator Heat from exhaust 0.0 kW Heat from radiation 0.0 kW Exhaust temperature 0 °C Cooling air flow 0.0 m³/min Combustion air flow 8.8 m³/min Exhaust gas flow 19.0 m³/min TA Luft N TA Luft TA Luft/2 EPA N	Fuel Cons. at 50% (P.R.P.)	11.3	l/h
Precision class Oil quantity 12.8 I Engine Antifreeze capacity Radiator type TR Heat from radiator Heat from exhaust Heat from radiation Cooling air flow Combustion air flow TA Luft TA Luft TA Luft/2 EPA Robit 12.8 I 12.8	Fuel Cons. at 25% (P.R.P.)	0.0	l/h
Oil quantity 12.8 I Engine Antifreeze capacity 8.5 I Radiator type TR Heat from radiator 0.0 kW Heat from exhaust 0.0 kW Heat from radiation 0.0 kW Exhaust temperature 0 °C Cooling air flow 0.0 m³/min Combustion air flow 8.8 m³/min Exhaust gas flow 19.0 m³/min TA Luft N TA Luft/2 N EPA N	Electronic regulator	Standard	
Engine Antifreeze capacity Radiator type TR Heat from radiator Heat from exhaust Cooling air flow Combustion air flow Exhaust gas flow TA Luft TA Luft/2 EPA TR Heat TR HO CO CO RW HO CO CO RW CO CO CO RW CO CO RW CO CO CO CO RW CO CO CO CO CO CO CO CO CO C	Precision class	G3	
Radiator type Heat from radiator Heat from exhaust O.0 kW Heat from radiation Exhaust temperature Cooling air flow Combustion air flow Exhaust gas flow TA Luft TA Luft TA Luft/2 EPA TR TO TR TR TR TR TR TR TR TR	Oil quantity	12.8	I
Heat from radiator Heat from exhaust Heat from exhaust Heat from radiation Consider the service of the serv	Engine Antifreeze capacity	8.5	1
Heat from exhaust 0.0 kW Heat from radiation 0.0 kW Exhaust temperature 0 °C Cooling air flow 0.0 m³/min Combustion air flow 8.8 m³/min Exhaust gas flow 19.0 m³/min TA Luft N TA Luft N TA Luft/2 N EPA N	Radiator type	TR	
Heat from radiation 0.0 kW Exhaust temperature 0 °C Cooling air flow 0.0 m³/min Combustion air flow 8.8 m³/min Exhaust gas flow 19.0 m³/min TA Luft N TA Luft/2 N EPA N	Heat from radiator	0.0	kW
Exhaust temperature 0 °C Cooling air flow 0.0 m³/min Combustion air flow 8.8 m³/min Exhaust gas flow 19.0 m³/min TA Luft N TA Luft/2 N EPA N	Heat from exhaust	0.0	kW
Cooling air flow Combustion air flow 8.8 m³/min Exhaust gas flow 19.0 m³/min TA Luft N TA Luft/2 EPA N	Heat from radiation	0.0	kW
Combustion air flow 8.8 m³/min Exhaust gas flow 19.0 m³/min TA Luft N TA Luft/2 N EPA N	Exhaust temperature	0	°C
Exhaust gas flow 19.0 m³/min TA Luft N TA Luft/2 N EPA N	Cooling air flow	0.0	m³/min
TA Luft N TA Luft/2 N EPA N	Combustion air flow	8.8	m³/min
TA Luft/2 N EPA N	Exhaust gas flow	19.0	m³/min
EPA N	TA Luft	N	
	TA Luft/2	N	
Stage 3	EPA	N	
-	Stage	3	

MAIN DATA		
Continuous power (PRP)	100.00	kVA
Continuous power (PRP)	80.00	kW
Emergency power (E.P.)	110.00	kVA
Emergency power (E.P.)	88.00	kW
VAC - HZ - cos(fi)	400 - 50 - 0.8	
Sound pressure 7 m.	67.0	dBA

DIMENSIONS AND WEIGHT		
Width	1040	mm
Length	2560	mm
Height	1805	mm
Weight	1600	kg

ALTERNATOR		
Description	STAMFORD	
Alternator model	UCI274C	
P.R.P. Power	100.0	kVA
E.P. Power	110.0	kVA
Connection	Series star	
Phases	3FN	
Winding	311	
Terminal Number	12	nr.
IP Protection	23	
Electronic regulator	AS440	
Precision	1.0	± %

BASEFRAME	
Model	GV060HD
Standard tank	160 I
Optional tank	70 I
Oversized tank*	800 I

CANOPY & SILENCER	
Canopy model	GV060
Silencer model	MSR/a 65
Silencer outlet diameter	76.0 mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance. P.R.P. Prime Power-Continuous power at variable load: The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer. E.P. - Emergency power: This is the maximum power that a generating set can deliver for a limited number of hours per year while complying with the maintenance frequency stipulated under the environmental conditions set by the Manufacturer. The number of hours per year is determined by the engine manufacturer. The average power output over time must be lower than the percentages set by the engine manufacturer. Overloading is not allowed.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.