


P 450 B





POWERFULL "B"



Stage

For illustrative purposes only		
ENGINE		
Description	PERKINS	
Engine model	2506A-E15TAG1	
Cylinders	6	
RPM speed	1800	
Cubic capacity	15.20	I
Air intake	Turbocharged	
Standard voltage	24	Vdc
Optional voltage		Vdc
Sae	1/2-14	
ВМЕР	2036	kPa
Cooling	Water	
Flywheel P.R.P. Power net	435.0	kW
Flywheel E.P. Power net	490.0	kW
Fuel Cons. at 100% (E.P.)	116.0	l/h
Fuel Cons. at 100% (P.R.P)	102.0	l/h
Fuel Cons. at 75% (P.R.P.)	78.0	l/h
Fuel Cons. at 50% (P.R.P.)	53.0	l/h
Fuel Cons. at 25% (P.R.P.)	0.0	l/h
Electronic regulator	Standard	
Precision class	G3	
Oil quantity	62.0	I
Engine Antifreeze capacity	58.0	1
Radiator type	TR	
Heat from radiator	143.0	kW
Heat from exhaust	310.0	kW
Heat from radiation	30.5	kW
Exhaust temperature	550	°C
Cooling air flow	866.0	m³/min
Combustion air flow	34.3	m³/min
Exhaust gas flow	96.0	m³/min
TA Luft	N	
TA Luft/2	N	
EPA	N	

MAIN DATA		
Continuous power (PRP)	500.00 kVA	
Continuous power (PRP)	400.00 kW	
Emergency power (E.P.)	563.00 kVA	
Emergency power (E.P.)	450.40 kW	
VAC - HZ - cos(fi)	208 - 60 - 0.8	

DIMENSIONS AND WEIGHT		
Width	1260	mm
Length	3400	mm
Height	2200	mm
Weight	4000	kg

ALTERNATOR	
Description	STAMFORD
Alternator model	S4L1D-G
P.R.P. Power	500.0 kVA
E.P. Power	565.0 kVA
Connection	Parallel star
Phases	3FN
Winding	311
Terminal Number	12 nr.
IP Protection	23
Electronic regulator	AS440
Precision	1.0 ± %

BASEFRAME	
Model	T3
Standard tank	900 I
Optional tank	0
Oversized tank*	0 1

CANOPY & SILENCER		
Canopy model	SENZA COFANO	
Silencer model	MS 35	
Silencer outlet diameter	168.0 mm	

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%. atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound obsorbiolal. Tele Consumption is infinite and refers to specific weight 0,50kg/i. Southern power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance. P.R.P. Prime Power-Continuous power at variable load: dimensions, performance. P.R.P. Prime Power-Continuous power at variable load: The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer. E.P. - Emergency power: This is the maximum power that a generating set can deliver for a limited number of hours per year while complying with the maintenance frequency stipulated under the environmental conditions set by the Manufacturer. The number of hours per year is determined by the engine manufacturer. The average power output over time must be lower than the percentages set by the engine manufacturer. Overloading is not allowed.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.