## **TECHNICAL DATASHEET BD 51 B**




## **BD 51 B**





## POWERFULL "B"



For illustrative purposes only

To mustrative purposes only		
ENGINE		
Description	BAUDOUIN	
Engine model	4M06G10D0/S	
Cylinders	4	
RPM speed	1500	
Cubic capacity	2.30	I
Air intake	Turbocharged	
Standard voltage	12	Vdc
Optional voltage		Vdc
Sae	3-11½	
ВМЕР	1843	kPa
Cooling	Water	
Flywheel P.R.P. Power net	46.2	kW
Flywheel E.P. Power net	51.2	kW
Fuel Cons. at 100% (E.P.)	13.3	l/h
Fuel Cons. at 100% (P.R.P)	11.9	l/h
Fuel Cons. at 75% (P.R.P.)	8.9	l/h
Fuel Cons. at 50% (P.R.P.)	6.0	l/h
Fuel Cons. at 25% (P.R.P.)	3.2	l/h
Electronic regulator	Standard	
Precision class	G2	
Oil quantity	9.2	I
Engine Antifreeze capacity	5.0	I
Radiator type	TR	
Heat from radiator	0.0	kW
Heat from exhaust	0.0	kW
Heat from radiation	0.0	kW
Exhaust temperature	550	°C
Cooling air flow	102.0	m³/min
Combustion air flow	2.7	m³/min
Exhaust gas flow	9.7	m³/min
TA Luft	N	
TA Luft/2	N	
EPA	N	
Stage	N	

MAIN DATA	
Continuous power (PRP)	<b>50.00</b> kVA
Continuous power (PRP)	<b>40.00</b> kW
Emergency power (E.P.)	<b>55.00</b> kVA
Emergency power (E.P.)	<b>44.00</b> kW
VAC - HZ - cos(fi)	400 - 50 - 0.8

DIMENSIONS AND WEIGHT		
Width	890	mm
Length	1670	mm
Height	1250	mm
Weight	750	kg

ALTERNATOR		
Description	STAMFORD	
Alternator model	S1L2-Y	
P.R.P. Power	62.5	kVA
E.P. Power	68.8	kVA
Connection	Series star	
Phases	3FN	
Winding	311	
Terminal Number	12	nr.
IP Protection	23	
Electronic regulator	AS540	
Precision	1.0	± %

BASEFRAME	
Model	T1
Standard tank	160 I
Optional tank	0 1
Oversized tank*	0

CANOPY & SILENCER		
Canopy model	SENZA COFANO	
Silencer model	MS 12	
Silencer outlet diameter	60.0	mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance. P.R.P. Prime Power-Continuous power at variable load: The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer. E.P. - Emergency power: This is the maximum power that a generating set can deliver for a limited number of hours per year while complying with the maintenance frequency stipulated under the environmental conditions set by the Manufacturer. The number of hours per year is determined by the engine manufacturer. The average power output over time must be lower than the percentages set by the engine manufacturer. Overloading is not allowed.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.