TECHNICAL DATASHEET P 1050 CO



P 1050 CO





POWERFULL "CO"



For illustrative purposes only

MAIN DATA	
Continuous power (PRP)	1030.00 kVA
Continuous power (PRP)	824.00 kW
Emergency power (E.P.)	1110.00 kVA
Emergency power (E.P.)	888.00 kW
VAC - HZ - cos(fi)	400 - 50 - 0.8

DIMENSIONS AND WEIGHT

		_
ENGINE		
Description	PERKINS	
Engine model	4008TAG2A	
Cylinders	8	
RPM speed	1500	
Cubic capacity	30.56	I
Air intake	Turbocharged	
Standard voltage	24	Vdc
Optional voltage		Vdc
Sae	0-18	
BMEP	2320	kPa
Cooling	Water	
Flywheel P.R.P. Power net	878.0	kW
Flywheel E.P. Power net	964.0	kW
Fuel Cons. at 100% (E.P.)	248.0	l/h
Fuel Cons. at 100% (P.R.P)	220.0	l/h
Fuel Cons. at 75% (P.R.P.)	160.0	l/h
Fuel Cons. at 50% (P.R.P.)	108.0	l/h
Fuel Cons. at 25% (P.R.P.)	57.0	l/h
Electronic regulator	Standard	
Precision class	G3	
Oil quantity	165.6	I
Engine Antifreeze capacity	48.0	I
Radiator type	TR	
Heat from radiator	332.0	kW
Heat from exhaust	698.0	kW
Heat from radiation	80.0	kW
Exhaust temperature	438	°C
Cooling air flow	1290.0	m³/min
Combustion air flow	75.0	m³/min
Exhaust gas flow	200.0	m³/min
TA Luft	N	
TA Luft/2	N	
EPA	N	
Stage	N	
The data countries districted as		

ALTERNATOR		
Description	STAMFORD	
Alternator model	HCI6J	
P.R.P. Power	1030.0	kVA
E.P. Power	1110.0	kVA
Connection	Star	
Phases	3FN	
Winding	312	
Terminal Number	6	nr.
IP Protection	23	
Electronic regulator	MX322	
Precision	0.5	± %

BASEFRAME	
Model	ST60
Standard tank	0 1
Optional tank	0 1
Oversized tank*	0 1

CANOPY & SILENCER		
Canopy model	CONTAINER 40 FT HIGH CUBE	
Silencer model		
Silencer outlet diameter	0.0	mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0.850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance. P.R.P. Prime Power-Continuous power at variable load: The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer: according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer. E.P. - Emergency power: This is the maximum power that a generating set can deliver for a limited number of hours per year while complying with the maintenance frequency stipulated under the environmental conditions set by the Manufacturer. The number of hours per year is determined by the engine manufacturer. The average power output over time must be lower than the percentages set by the engine manufacturer. Overloading is not allowed.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.