



For illustrative purposes only

Strong points

- 1- Industrial diesel engine in genset version with certificate of origin
 - 2- Industrial brushless alternator with AVR
 - 3- Steel baseframe with retention basin, fuel tank with level sensor
 - 4- Soundproof canopy in galvanised, power coated sheet steel
 - 5- Soundproofing material made of high attenuation polyester fibre
 - 6- Exhaust silencer with insulated manifold
 - 7- Electrical panel mounted on board the unit with digital control device installed in metal box
 - 8- Compact for easy handling and use
 - 9- Test report, manuals and electrical drawings supplied
 - 10- World wide after sales service and technical support
- Further details on the technical data sheet**

Performance

Continuous power (PRP)	950.0	(kVA)
Continuous power (PRP)	760.0	(kW)
Stand-by power (LTP)	1038.0	(kVA)
Stand-by power (LTP)	830.4	(kW)
Power factor	0.8	

Voltage

Frequency (Hz)	50	Hz
Voltage (V)	380	V

Dimensions and noise level

Width	2200	mm
Length	8600	mm
Height	3200	mm
Weight	11710	kg
Sound pressure 7 m.	70.0	dBA

Data references

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

P.R.P. Prime Power-Continuous power at variable load: The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer, according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.
L.T.P. Limited-time running power-Limited power: The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

Engine

Engine brand	PERKINS
Engine model	4008TAG2A
Cylinders	8
Speed	1500 r.p.m.
Cubic capacity	30.56 l
Air intake	Turbocharged
Standard voltage	24 Vdc
Optional voltage	Vdc
Sae	0-18
BMEP	2320 kPa
Cooling	Water

Engine power

Flywheel P.R.P. Power	872.0	kW
Flywheel Stand-by Power	958.0	kW

Fuel consumption

Fuel Cons. at 100% (L.T.P.)	248.0	l/h
Fuel Cons. at 100% (P.R.P.)	220.0	l/h
Fuel Cons. at 75% (P.R.P.)	160.0	l/h
Fuel Cons. at 50% (P.R.P.)	108.0	l/h
Fuel Cons. at 25% (P.R.P.)	57.0	l/h

Speed regulation

Electronic regulator	Standard
Precision class	G2

Engine dimensions and liquids

Oil quantity	165.6	l
Engine Antifreeze capacity	48.0	l
Radiator standard	PTE4008	

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.



Heat from engine

Heat from radiator	332.0 kW
Heat from exhaust	698.0 kW
Heat from radiation	80.0 kW

Exhaust data

Exhaust temperature	438 °C
Cooling air flow	0.00 m ³ /min
Combustion air flow	75.00 m ³ /min
Exhaust gas flow	200.00 m ³ /min

Emissions

TA Luft	Not available
TA Luft/2	Not available
EPA	Not available
Stage	Not available

Alternator

Alternator brand	MECC ALTE
Alternator model	ECO43-1M/4
P.R.P. Power	950.0 kVA
L.T.P. Power	1038.0 kVA

Alternator wirings

Connection	Parallel star
Phases	3PH+N
Winding	12 terminals 800 V
Terminal Number	12 nr.

Alternator protection

IP Protection	23
---------------	----

Voltage regulator

Electronic regulator	DER-1
Precision	1.0 ± %

Baseframe

Model	ST60
Standard tank	0 l
Optional tank	0 l
Oversized tank*	0 l

Canopy & Silencer

Canopy model	C60
Silencer model	MSR/a 150
Silencer outlet diameter	168.0 mm

Available control panels



Advanced **single gen-set controller for stand-by and prime power applications**. Direct communication with EFI engines, total remote monitoring and control, easy to install, configure and use, wide range of communication capabilities including: connection via RS232, RS485, CAN and on board USB, internet access using Ethernet, GPRS or 4G support for Modbus and SNMP protocols. Internal PLC support with PLC editor and monitor included in LiteEdit, cloud-based monitoring and control via Onis Visa WebSupervisor, active SMS and emails in different languages, SNMP traps, geofencing and tracking via Onis Visa WebSupervisor, 2x 10 A binary outputs for cranking and fuel solenoid, option for up to 16 additional binary inputs/outputs, flexible event based history with up to 350 events, load shedding, dummy load capability, tier 4 final support, automatic temperature based cooling/heating, comprehensive gen-set protections, multipurpose flexible timers, true RMS measurement.

Optional control panels



Guard Touch MANUAL OR AUTOMATIC is the new revolutionary controller with touch screen, researched and developed by Visa S.p.A., which will be standard supply on our gensets. From a technical and operational viewpoint, the new device is different from its predecessors, but still maintains Visa's main characteristic: MODULARITY! Guard Touch is a versatile controller able to satisfy the myriad of requests from the end-user, from manual function to totally automatic management.

Options

Each genset model has a wide range of accessories and customised equipment choices; standard equipment and optional accessories are described in the technical data sheet. Contact our sales office for further information and details.

