


**CRICKET "CK"**


For illustrative purposes only

**ENGINE**

Engine brand	PERKINS
Engine model	1106A-70TAG2
Cylinders	6
Speed	1800 r.p.m.
Cubic capacity	7.01 l
Air intake	Turbocharged
Standard voltage	12 Vdc
Sae	3-11½
BMEP	1478 kPa
Cooling	Water
Flywheel P.R.P. Power	147.4 kW
Flywheel Stand-by Power	163.8 kW
Fuel Cons. at 100% (L.T.P.)	41.7 l/h
Fuel Cons. at 100% (P.R.P.)	38.2 l/h
Fuel Cons. at 75% (P.R.P.)	29.1 l/h
Fuel Cons. at 50% (P.R.P.)	19.1 l/h
Fuel Cons. at 25% (P.R.P.)	11.0 l/h
Electronic regulator	On request
Precision class	G2
Oil quantity	16.5 l
Engine Antifreeze capacity	9.5 l
Radiator type	Tropical
Heat from radiator	112.7 kW
Heat from exhaust	120.6 kW
Heat from radiation	12.3 kW
Exhaust temperature	407 °C
Cooling air flow	245.00 m³/min
Combustion air flow	14.97 m³/min
Exhaust gas flow	32.29 m³/min
TA Luft	Not available
TA Luft/2	Not available
EPA	Not available
Stage	Not available

**MAIN DATA**

Continuous power (PRP)	170.0 (kVA)
Continuous power (PRP)	136.0 (kW)
Stand-by power (LTP)	187.0 (kVA)
Stand-by power (LTP)	149.6 (kW)
Voltage • Frequency • Power Factor	380V • 60Hz • 0.8 cosφ
Sound pressure 7 m.	78.0 dBA

**DIMENSIONS AND WEIGHT**

Width	1150 mm
Length	2944 mm
Height	1870 mm
Weight	2020 kg

**ALTERNATOR**

Alternator brand	STAMFORD
Alternator model	UCI274G
P.R.P. Power	180.0 kVA
L.T.P. Power	194.0 kVA
Connection	Series star
Phases	3PH+N
Winding	12 terminals Winding 311
Terminal Number	12 nr.
IP Protection	23
Electronic regulator	SX460
Precision	1.5 ± %

**BASEFRAME**

Model	CK40
Standard tank	280 l
Optional tank	0 l
Oversized tank*	0 l

**CANOPY & SILENCER**

Canopy model	CK40
Silencer model	MSR/a 80
Silencer outlet diameter	89.0 mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

**P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

**L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

