




GALAXY "GX"



For illustrative purposes only

ENGINE

Engine brand	VOLVO-PENTA
Engine model	TWD1645GE
Cylinders	6
Speed	1800 r.p.m.
Cubic capacity	16.12 l
Air intake	Turbocharged
Standard voltage	24 Vdc
Optional voltage	Vdc
Sae	1-14
BMEP	2700 kPa
Cooling	Water
Flywheel P.R.P. Power	619.0 kW
Flywheel Stand-by Power	681.0 kW
Fuel Cons. at 100% (L.T.P.)	163.2 l/h
Fuel Cons. at 100% (P.R.P.)	149.0 l/h
Fuel Cons. at 75% (P.R.P.)	114.1 l/h
Fuel Cons. at 50% (P.R.P.)	79.9 l/h
Fuel Cons. at 25% (P.R.P.)	44.9 l/h
Electronic regulator	Standard
Precision class	G3
Oil quantity	48.0 l
Engine Antifreeze capacity	25.0 l
Radiator type	Tropical
Heat from radiator	403.0 kW
Heat from exhaust	513.0 kW
Heat from radiation	27.0 kW
Exhaust temperature	497 °C
Cooling air flow	804.00 m ³ /min
Combustion air flow	47.63 m ³ /min
Exhaust gas flow	115.00 m ³ /min
TA Luft	Not available
TA Luft/2	Not available
EPA	Not available
Stage	Not available

MAIN DATA

Continuous power (PRP)	730.0 (kVA)
Continuous power (PRP)	584.0 (kW)
Stand-by power (LTP)	800.0 (kVA)
Stand-by power (LTP)	640.0 (kW)
Voltage • Frequency • Power Factor	208V • 60Hz • 0.8 cosφ
Sound pressure 7 m.	0.0 dBA

DIMENSIONS AND WEIGHT

Width	N/D mm
Length	N/D mm
Height	N/D mm
Weight	0 kg

ALTERNATOR

Alternator brand	STAMFORD
Alternator model	HCI5F
P.R.P. Power	738.0 kVA
L.T.P. Power	806.0 kVA
Connection	Parallel star
Phases	3PH+N
Winding	12 terminals Winding 311
Terminal Number	12 nr.
IP Protection	23
Electronic regulator	AS440
Precision	1.0 ± %

BASEFRAME

Model	GV201
Standard tank	950 l
Optional tank	120 l
Oversized tank*	0 l

CANOPY & SILENCER

Canopy model	GV201
Silencer model	MSR/a 150
Silencer outlet diameter	168.0 mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

P.R.P. Prime Power-Continuous power at variable load: The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

L.T.P. Limited-time running power-Limited power: The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.

