



CRICKET "CK"



For illustrative purposes only

ENGINE

Engine brand	FPT IVECO
Engine model	N67TM7
Cylinders	6
Speed	1800 r.p.m.
Cubic capacity	6.70 l
Air intake	Turbocharged
Standard voltage	12 Vdc
Sae	3-11«
BMEP	1841 kPa
Cooling	Water
Flywheel P.R.P. Power	170.0 kW
Flywheel Stand-by Power	187.0 kW
Fuel Cons. at 100% (L.T.P.)	48.9 l/h
Fuel Cons. at 100% (P.R.P.)	45.5 l/h
Fuel Cons. at 75% (P.R.P.)	38.0 l/h
Fuel Cons. at 50% (P.R.P.)	22.7 l/h
Fuel Cons. at 25% (P.R.P.)	0.0 l/h
Electronic regulator	On request
Precision class	
Oil quantity	17.2 l
Engine Antifreeze capacity	25.5 l
Radiator type	Tropical
Heat from radiator	113.4 kW
Heat from exhaust	139.4 kW
Heat from radiation	16.6 kW
Exhaust temperature	495 °C
Cooling air flow	336.00 m ³ /min
Combustion air flow	11.00 m ³ /min
Exhaust gas flow	37.00 m ³ /min
TA Luft	Not available
TA Luft/2	Not available
EPA	Not available
Stage	Not available

MAIN DATA

Continuous power (PRP)	200.0 (kVA)
Continuous power (PRP)	160.0 (kW)
Stand-by power (LTP)	225.0 (kVA)
Stand-by power (LTP)	180.0 (kW)
Voltage • Frequency • Power Factor	208V • 60Hz • 0.8 cosφ

DIMENSIONS AND WEIGHT

Width	1150 mm
Length	2944 mm
Height	1870 mm
Weight	1870 kg

ALTERNATOR

Alternator brand	STAMFORD
Alternator model	UCI274H
P.R.P. Power	237.5 kVA
L.T.P. Power	256.3 kVA
Connection	Parallel star
Phases	3P+N
Winding	12 terminals Winding 311
Terminal Number	12 nr.
IP Protection	23
Electronic regulator	AS440
Precision	1.0 ± %

BASEFRAME

Model	CK40
Standard tank	280 l
Optional tank	0 l
Oversized tank*	0 l

CANOPY & SILENCER

Canopy model	CK40
Silencer model	MSR/a 80
Silencer outlet diameter	89.0 mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0.850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

P.R.P. Prime Power-Continuous power at variable load: The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

L.T.P. Limited-time running power-Limited power: The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.

