



### GALAXY "GO"



For illustrative purposes only

#### ENGINE

Engine brand	DEUTZ
Engine model	BF4M2011C
Cylinders	4
Speed	1500 r.p.m.
Cubic capacity	3.11 l
Air intake	Turbocharged
Standard voltage	12 Vdc
Optional voltage	24 Vdc
Sae	3-11½
BMEP	1520 kPa
Cooling	Oil
Flywheel P.R.P. Power	51.2 kW
Flywheel Stand-by Power	54.0 kW
Fuel Cons. at 100% (L.T.P.)	14.9 l/h
Fuel Cons. at 100% (P.R.P.)	14.2 l/h
Fuel Cons. at 75% (P.R.P.)	10.4 l/h
Fuel Cons. at 50% (P.R.P.)	7.0 l/h
Fuel Cons. at 25% (P.R.P.)	3.9 l/h
Electronic regulator	On request
Precision class	G2
Oil quantity	13.0 l
Engine Antifreeze capacity	0.0 l
Radiator type	
Heat from radiator	28.3 kW
Heat from exhaust	0.0 kW
Heat from radiation	7.9 kW
Exhaust temperature	570 °C
Cooling air flow	53.30 m³/min
Combustion air flow	4.00 m³/min
Exhaust gas flow	11.70 m³/min
TA Luft	Not available
TA Luft/2	Not available
EPA	Not available
Stage	Stage 2

#### MAIN DATA

Continuous power (PRP)	60.0 (kVA)
Continuous power (PRP)	48.0 (kW)
Stand-by power (LTP)	62.0 (kVA)
Stand-by power (LTP)	49.6 (kW)
Voltage • Frequency • Power Factor	380V • 50Hz • 0.8 cosφ
Sound pressure 7 m.	0.0 dBA

#### DIMENSIONS AND WEIGHT

Width	1040 mm
Length	2200 mm
Height	1460 mm
Weight	980 kg

#### ALTERNATOR

Alternator brand	MARELLI
Alternator model	MJB200MA4
P.R.P. Power	61.5 kVA
L.T.P. Power	67.6 kVA
Connection	Series star
Phases	3PH+N
Winding	12 terminals 50-60Hz Winding M0
Terminal Number	12 nr.
IP Protection	23
Electronic regulator	M16FA655A
Precision	0.5 ± %

#### BASEFRAME

Model	GV030HD
Standard tank	160 l
Optional tank	70 l
Oversized tank*	0 l

#### CANOPY & SILENCER

Canopy model	SENZA COFANO
Silencer model	MS 10
Silencer outlet diameter	48.0 mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

**P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

**L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

