



GALAXY "GO"



For illustrative purposes only

ENGINE

Engine brand	PERKINS
Engine model	2506C-E15TAG2
Cylinders	6
Speed	1500 r.p.m.
Cubic capacity	15.20 l
Air intake	Turbocharged
Standard voltage	24 Vdc
Optional voltage	Vdc
Sae	½-14
BMEP	2405 kPa
Cooling	Water
Flywheel P.R.P. Power	435.0 kW
Flywheel Stand-by Power	478.0 kW
Fuel Cons. at 100% (L.T.P.)	114.0 l/h
Fuel Cons. at 100% (P.R.P.)	106.0 l/h
Fuel Cons. at 75% (P.R.P.)	81.0 l/h
Fuel Cons. at 50% (P.R.P.)	55.0 l/h
Fuel Cons. at 25% (P.R.P.)	0.0 l/h
Electronic regulator	Standard
Precision class	G3
Oil quantity	62.0 l
Engine Antifreeze capacity	0.0 l
Radiator type	Tropical
Heat from radiator	175.0 kW
Heat from exhaust	362.0 kW
Heat from radiation	36.2 kW
Exhaust temperature	550 °C
Cooling air flow	722.00 m³/min
Combustion air flow	35.80 m³/min
Exhaust gas flow	94.00 m³/min
TA Luft	Not available
TA Luft/2	Not available
EPA	Not available
Stage	Stage 2

MAIN DATA

Continuous power (PRP)	500.0 (kVA)
Continuous power (PRP)	400.0 (kW)
Stand-by power (LTP)	546.0 (kVA)
Stand-by power (LTP)	436.8 (kW)
Voltage • Frequency • Power Factor	380V • 50Hz • 0.8 cosφ
Sound pressure 7 m.	0.0 dBA

DIMENSIONS AND WEIGHT

Width	1820 mm
Length	4500 mm
Height	2220 mm
Weight	4460 kg

ALTERNATOR

Alternator brand	MECC ALTE
Alternator model	ECO40-3S/4
P.R.P. Power	500.0 kVA
L.T.P. Power	546.0 kVA
Connection	Series star
Phases	3PH+N
Winding	12 terminals std
Terminal Number	12 nr.
IP Protection	23
Electronic regulator	DER-1
Precision	1.0 ± %

BASEFRAME

Model	GV200
Standard tank	950 l
Optional tank	120 l
Oversized tank*	0 l

CANOPY & SILENCER

Canopy model	SENZA COFANO
Silencer model	MS 35
Silencer outlet diameter	168.0 mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

P.R.P. Prime Power-Continuous power at variable load: The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

L.T.P. Limited-time running power-Limited power: The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.

