



### POWERFULL "S"



For illustrative purposes only

#### ENGINE

Engine brand	PERKINS
Engine model	4012-46TAG3A
Cylinders	12
Speed	1500 r.p.m.
Cubic capacity	45.84 l
Air intake	Turbocharged
Standard voltage	24 Vdc
Optional voltage	Vdc
Sae	00-18
BMEP	2603 kPa
Cooling	Water
Flywheel P.R.P. Power	1436.0 kW
Flywheel Stand-by Power	1579.0 kW
Fuel Cons. at 100% (L.T.P.)	405.0 l/h
Fuel Cons. at 100% (P.R.P.)	370.0 l/h
Fuel Cons. at 75% (P.R.P.)	275.0 l/h
Fuel Cons. at 50% (P.R.P.)	187.0 l/h
Fuel Cons. at 25% (P.R.P.)	0.0 l/h
Electronic regulator	Standard
Precision class	G2
Oil quantity	177.0 l
Engine Antifreeze capacity	73.0 l
Radiator type	Temperate
Heat from radiator	510.0 kW
Heat from exhaust	1102.0 kW
Heat from radiation	110.0 kW
Exhaust temperature	480 °C
Cooling air flow	1920.00 m <sup>3</sup> /min
Combustion air flow	125.00 m <sup>3</sup> /min
Exhaust gas flow	350.00 m <sup>3</sup> /min
TA Luft	On request
TA Luft/2	On request
EPA	Not available
Stage	Not available

#### MAIN DATA

Continuous power (PRP)	1705.0 (kVA)
Continuous power (PRP)	1364.0 (kW)
Stand-by power (LTP)	0.0 (kVA)
Stand-by power (LTP)	0.0 (kW)
Voltage • Frequency • Power Factor	380V • 50Hz • 0.8 cosφ
Sound pressure 7 m.	78.0 dBA

#### DIMENSIONS AND WEIGHT

Width	2900 mm
Length	9380 mm
Height	3550 mm
Weight	15500 kg

#### ALTERNATOR

Alternator brand	MARELLI
Alternator model	MJB450LB4
P.R.P. Power	1830.0 kVA
L.T.P. Power	0.0 kVA
Connection	Star
Phases	3PH+N
Winding	6 terminals 400 Winding 80
Terminal Number	6 nr.
IP Protection	23
Electronic regulator	M31FA600A
Precision	0.5 ± %

#### BASEFRAME

Model	ST60
Standard tank	0 l
Optional tank	0 l
Oversized tank*	0 l

#### CANOPY & SILENCER

Canopy model	C60/08/01
Silencer model	----
Silencer outlet diameter	0.0 mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

**P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

**L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.

