



**GALAXY "GO"**


For illustrative purposes only

**ENGINE**

Engine brand	PERKINS
Engine model	1106A-70TG1
Cylinders	6
Speed	1500 r.p.m.
Cubic capacity	7.01 l
Air intake	Turbocharged
Standard voltage	12 Vdc
Optional voltage	Vdc
Sae	3-11½
BMEP	1412 kPa
Cooling	Water
Flywheel P.R.P. Power	118.7 kW
Flywheel Stand-by Power	131.9 kW
Fuel Cons. at 100% (L.T.P.)	33.8 l/h
Fuel Cons. at 100% (P.R.P.)	30.3 l/h
Fuel Cons. at 75% (P.R.P.)	22.7 l/h
Fuel Cons. at 50% (P.R.P.)	15.9 l/h
Fuel Cons. at 25% (P.R.P.)	9.0 l/h
Electronic regulator	On request
Precision class	G2
Oil quantity	16.5 l
Engine Antifreeze capacity	9.5 l
Radiator type	Tropical
Heat from radiator	82.0 kW
Heat from exhaust	102.0 kW
Heat from radiation	15.3 kW
Exhaust temperature	576 °C
Cooling air flow	182.00 m³/min
Combustion air flow	8.09 m³/min
Exhaust gas flow	22.66 m³/min
TA Luft	Not available
TA Luft/2	Not available
EPA	Not available
Stage	Not available

**MAIN DATA**

Continuous power (PRP)	135.0 (kVA)
Continuous power (PRP)	108.0 (kW)
Stand-by power (LTP)	150.0 (kVA)
Stand-by power (LTP)	120.0 (kW)
Voltage • Frequency • Power Factor	400V • 50Hz • 0.8 cosφ
Sound pressure 7 m.	0.0 dBA

**DIMENSIONS AND WEIGHT**

Width	1140 mm
Length	3000 mm
Height	1780 mm
Weight	1750 kg

**ALTERNATOR**

Alternator brand	STAMFORD
Alternator model	UCI274E
P.R.P. Power	140.0 kVA
L.T.P. Power	150.0 kVA
Connection	Series star
Phases	3PH+N
Winding	12 terminals Winding 311
Terminal Number	12 nr.
IP Protection	23
Electronic regulator	SX460
Precision	1.5 ± %

**BASEFRAME**

Model	GV100HD
Standard tank	360 l
Optional tank	120 l
Oversized tank*	800 l

**CANOPY & SILENCER**

Canopy model	SENZA COFANO
Silencer model	MS 20
Silencer outlet diameter	89.0 mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

**P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

**L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.

