

F 105 GXLVM



GALAXY "GX"



For illustrative purposes only

ENGINE

Description	FPT IVECO
Engine model	F36ETVP03
Cylinders	4
RPM speed	1500
Cubic capacity	3.60 l
Air intake	Turbocharged
Standard voltage	12 Vdc
Optional voltage	24 Vdc
Sae	3-11
BMEP	2610 kPa
Cooling	Water
Flywheel P.R.P. Power net	84.8 kW
Flywheel Stand-by Power net	93.4 kW
Fuel Cons. at 100% (E.P.)	23.8 l/h
Fuel Cons. at 100% (P.R.P.)	21.8 l/h
Fuel Cons. at 75% (P.R.P.)	15.8 l/h
Fuel Cons. at 50% (P.R.P.)	10.7 l/h
Fuel Cons. at 25% (P.R.P.)	6.1 l/h
Electronic regulator	Standard
Precision class	G3
Oil quantity	9.5 l
Engine Antifreeze capacity	5.0 l
Radiator type	TR
Heat from radiator	0.0 kW
Heat from exhaust	73.5 kW
Heat from radiation	13.0 kW
Exhaust temperature	740 °C
Cooling air flow	108.0 m³/min
Combustion air flow	7.6 m³/min
Exhaust gas flow	0.0 m³/min
TA Luft	N
TA Luft/2	N
EPA	N
Stage	5

MAIN DATA

Continuous power (PRP)	100.00 kVA
Continuous power (PRP)	80.00 kW
Emergency power (E.P.)	110.00 kVA
Emergency power (E.P.)	88.00 kW
VAC - HZ - cos(fi)	400 - 50 - 0.8
Sound pressure 7 m.	65 ± 3 dBA

DIMENSIONS AND WEIGHT

Width	1140 mm
Length	3060 mm
Height	2200 mm
Weight	1910 kg

ALTERNATOR

Description	LEROY SOMER
Alternator model	TAL044D
P.R.P. Power	100 kVA
E.P. Power	110 kVA
Connection	Series star
Phases	3FN
Winding	6
Terminal Number	12 nr.
IP Protection	23
Electronic regulator	R180
Precision	1 ± %

BASEFRAME

Model	GV100HD
Standard tank	360 l

SOCKET KIT

Custom Socket kit - Rental version	optional
------------------------------------	----------

CANOPY & SILENCER

Canopy model	GV100
Silencer model	MSR/a 80
Silencer outlet diameter	89 mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

P.R.P. Prime Power-Continuous power at variable load: The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer, according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

E.P. - Emergency power: This is the maximum power that a generating set can deliver for a limited number of hours per year while complying with the maintenance frequency stipulated under the environmental conditions set by the Manufacturer. The number of hours per year is determined by the engine manufacturer. The average power output over time must be lower than the percentages set by the engine manufacturer. Overloading is not allowed.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.

