

**GALAXY "GX"**


For illustrative purposes only

**ENGINE**

Description	FPT IVECO
Engine model	N67TEVP05
Cylinders	6
RPM speed	1500
Cubic capacity	6.70 l
Air intake	Turbocharged
Standard voltage	24 Vdc
Optional voltage	Vdc
Sae	3-11
BMEP	0 kPa
Cooling	Water
Flywheel P.R.P. Power net	176.0 kW
Flywheel Stand-by Power net	195.0 kW
Fuel Cons. at 100% (L.T.P.)	47.4 l/h
Fuel Cons. at 100% (P.R.P.)	43.0 l/h
Fuel Cons. at 75% (P.R.P.)	31.9 l/h
Fuel Cons. at 50% (P.R.P.)	21.3 l/h
Fuel Cons. at 25% (P.R.P.)	0.0 l/h
Electronic regulator	Standard
Precision class	G3
Oil quantity	18.0 l
Engine Antifreeze capacity	12.6 l
Radiator type	TR
Heat from radiator	112.6 kW
Heat from exhaust	156.3 kW
Heat from radiation	14.4 kW
Exhaust temperature	550 °C
Cooling air flow	0.0 m <sup>3</sup> /min
Combustion air flow	11.3 m <sup>3</sup> /min
Exhaust gas flow	38.1 m <sup>3</sup> /min
TA Luft	N
TA Luft/2	N
EPA	N
Stage	5

**MAIN DATA**

Continuous power (PRP)	<b>200.00</b> kVA
Continuous power (PRP)	<b>160.00</b> kW
Stand-by power (LTP)	<b>220.00</b> kVA
Stand-by power (LTP)	<b>176.00</b> kW
VAC - HZ - cos(fi)	<b>400 - 50 - 0.8</b>

**DIMENSIONS AND WEIGHT**

Width	1350 mm
Length	4500 mm
Height	2370 mm
Weight	3100 kg

**ALTERNATOR**

Description	STAMFORD
Alternator model	UCI274H
P.R.P. Power	200 kVA
L.T.P. Power	220 kVA
Connection	Series star
Phases	3FN
Winding	311
Terminal Number	12 nr.
IP Protection	23
Electronic regulator	AS440
Precision	1 ± %

**BASEFRAME**

Model	GV121
Standard tank	500 l

**CANOPY & SILENCER**

Canopy model	GV121
Silencer model	MSR/a 100
Silencer outlet diameter	114 mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0.850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

**P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer, according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.  
**L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.

