

ENCLOSURE TYPE: VM5 65



ALL PICTURES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY AND MAY SHOW OPTIONAL EQUIPMENT. ACTUAL PRODUCT MAY VARY DUE TO PRODUCT ENHANCEMENT.

MAIN DATA

Continuous Power (PRP)	60.0 kVA
Continuous Power (PRP)	48.0 kW
Stand-by Power (LTP)	60.0 kVA
Stand-by Power (LTP)	48.0 kW
Voltage · Frequency · Power Factor	400V·50Hz·0.8cosφ
Sound pressure 7 metres (±3dBA)	62.0 dBA

DIMENSIONS AND WEIGHT

Width	1080 mm
Length	2480 mm
Height	1710 mm
Weight (full fuel tank)	1850 kg

VM5 RANGE STANDARD EQUIPMENT

High-capacity Fuel Tank + Leak sensor + Tank cap with key,
Strong Forklift pockets & Central lifting hook,
Battery disconnecter & Adjustable earth fault relay,
GSM module + Antenna & Visa WebSupervisor App

GENERAL DATA

ENGINE		
Engine brand	DOOSAN	
Engine model	D34 STAGE V	
Cylinders	4	nr
Speed	1500	r.p.m.
Cubic capacity	3.4	l
Air intake	Turbocharged	
Standard voltage	12	Vdc
Optional voltage	-	Vdc
Sae	4-10	
BMEP	1600	kPa
Cooling	Water	
Flywheel P.R.P. Power	54.70	kW
Flywheel Stand-by Power	54.70	kW
Fuel Cons. at 100% (L.T.P.)	-	l/h
Fuel Cons. at 100% (P.R.P.)	13.90	l/h
Fuel Cons. at 75% (P.R.P.)	10.60	l/h
Fuel Cons. at 50% (P.R.P.)	7.30	l/h
Fuel Cons. at 25% (P.R.P.)	4.20	l/h
Engine speed regulator	Electronic	
Precision class	G3 - 0.50	
Oil quantity	12,60	l
Engine Antifreeze capacity	16,80	l
Heat from radiator	-	kW
Exhaust temperature	-	°C
Emissions	STAGE V	EU

ALTERNATOR		
Alternator brand	STAMFORD	
Alternator model	S1L2-Y1	
P.R.P. Power	60.0	kVA
L.T.P. Power	66,0	kVA
Connection	Series Star 3F+N	
Terminal Number	12	nr
IP Protection	23	
Electronic regulator	AS540	
Precision	1.0	+/-%

AUTONOMY		
Fuel tank	270	l
Hours of operation at 75% of load	25	h

CONTROL PANEL		
Controller Brand	COMAP	
Controller Model	AMF 25 - IL4	
Socket kit	1x125A - 1x63A - 1x32A - 1x16A - 1x Schuko	



Standard reference conditions: temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance. P.R.P. Prime Power-Continuous power at variable load: The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer. L.T.P. Limited-time running power-Limited power: The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.

