

**ONIS VISA Zeus Dry Prime****Model: MTZ.F175.SS****MODEL: Dewatering**

ALL PICTURES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

MAIN DATA

Max. flow	1589 m³/hour
Max. Max head	25 mwc
Solids handling	95 mm
Suction connection	DN300 PN10
Delivery connection	ANSI 12"
Fuel tank	850 l.

DIMENSIONS AND WEIGHT

Width	2086 mm
Length	4300 mm
Height	2497 mm
Weight	** Kg (approx)

The **Zeus Dry Prime** range delivers fast dewatering solutions to sites where a power source is not available. Using a Pioneer pump featuring a 100% mechanical priming system, the Zeus Dry Prime motorpumps quickly prime and reprime, even from dry conditions.

PUMP

Brand	Pioneer
Model	PP1212S17T E0 311
Pump casing:	65-42-12 ductile iron with 280 BHN hardness
Enclosed impeller:	CA6NM Self-hardening Stainless Steel with 13% chromium with 360BHN hardness
Pump shaft:	1144 Stress Proof Steel Chromed
Bearings:	Dual angular contact drive end bearings
Priming system:	Mechanically Driven Diaphragm Style vacuum pump
Air removal capab.:	2 x 50 cfm (170 m ³ /h)
Float box:	Single chamber with positive sealing air separation. Stainless steel float ball and linkage
Discharge Check Valve:	Swing Style – ductile iron with Buna-n Disc

ENGINE

Brand	FPT Industrial
Model	N67MNTX20.50
Gross Power	129 kW @ 2200 rev/min
Displacement	6,7 l.
N° cylinders	6
Cooling system	Water cooled
Exhaust emission	Stage IIIA


CONTROL PANELController model **NT5 by Nettuno**

Auto start/stop system
Switch manual – 0 – Automatic
Tachometer
Hour counter
Warning lights “oil and engine temperature”
Warning light “auto stand-by”
GPRS – VISA Web supervisor & APP
Geolocation and Geo-fencing
Soot / Ash filter control
Two float switches (min/max level) support for automatic operation


The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice.

**ONIS VISA Zeus Dry Prime****Model: MTZ.F175.SS****MULTI-SPEED PERFORMANCE CURVE**

World-class performance: Using high efficiency pumps and top performance diesel engines, the Zeus Dry Prime units offer high performance and efficiency to ensure predictable and timely job completion with minimal operating expenses



The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice.

PRELIMINARY DIMENSIONS


Nettuno motorpumps designed & built by VISA SPA • Complete in-house design & production

- Over 45 years of experience in the motorpumps sector
- In-house extensive testing facility
- Modern & functional design
- Durable materials
- Customizations available

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice.